

ECLEREO
AUDIO CREATIVE POWER



ECLEREO
ENTERTAINMENT SOUND SYSTEMS

Motors, 166-168 08038 Barcelona - Spain
Domestic sales / Ventas España (34) 902221400
Export sales / Ventas Export (34) 902331400
General calls (34) 932238403
Fax (34) 932238404
info@ecler.es / www.ecler.es

All the characteristics are subject to variation due to production tolerances.
ECLEREO reserves the right to make changes or improvements in manufacturing
or design without any notice.
Todos los datos son los que están en las especificaciones de los procesos de
producción.
ECLEREO se reserva el derecho de realizar cambios o mejoras en la fabricación
o diseño que no afecten a las especificaciones.

5
COMPACT
Universal
Mixer

COMPACT 5

Universal Mixer



A fully featured but compact and clearly designed 5 channel console to offer the most versatile mixing unit to installers and mobile P.A. Adapted to a very wide range of purposes such as Bars, Disco-bars, Religious Centres, Retail shops, Fitness rooms, Education Centres, Meeting rooms, Mobile P.A. rental etc ... where space is limited and users are non-technical people.

MAIN CHARACTERISTICS

- Versatile laptop and rack format design (3u. high / 19" rack).
- 5 channels, 8 LINE Inputs, 3 MIC Inputs, 2 PHONO Inputs.
- 2 independent MASTER (1x XLR / 1x RCA) and REC output.
- 3 band equalizer per channel.
- PFL monitoring. Talkover. Phantom power.
- 45mm ECLER faders per channel.

TECHNICAL CHARACTERISTICS

Inputs Sensitivity nom/Impedance	LINE (A-B-AUX IN)	0dBV/50k Ω
	PHONO	-40dBV/50k Ω
	MICRO (BAL)	-50dBV/>1k Ω
Outputs Level/Minimum Load	OUT 1 (BAL)	0dBV/600 Ω 1V
	OUT 2	0dBV/2.2k Ω 1V
	REC	0dBV/10k Ω
	HEADPHONES	230mW/400 Ω
Frequency Response	LINE	10Hz+30kHz -1dB
	MICRO BAL	10Hz+25kHz -1dB
	PHONO	RIAA \pm 0.5dB
THD+N	LINE	<0.01%
	MICRO	<0.1%
	PHONO	<0.2%
CMRR	MICRO	>70dB @ 1kHz
Signal Noise Ratio	LINE	>100dB
	MICRO	>85dB
	PHONO	>90dB
Gain control all inputs	GAIN	\pm 20dB
Tone control	BASS	100Hz \pm 12dB
	MID	1.8kHz \pm 15dB
	TREBLE	10kHz \pm 11dB
Talkover	TIME	0.3/3 seg
	EFFECT	0/-30 dB
Signal present indicators	LINE	-40dB
	MICRO	-90dB
Clip indicators		+10dB
Phantom voltage		+18VDC/5mA max
Mains		90-264VCA 47-63Hz
Power consumption		28VA
Dimensions		482.6x132.5x200mm
Weight		3.7kg

Channel 1	LINE A / LINE B	LINE B switchable to PHONO from back panel
Channel 2	LINE A / LINE B	LINE B switchable to PHONO from back panel
Channel 3	LINE / MICRO / AUXILIAR	AUXILIAR in front panel
Channel 4	LINE / MICRO	-
Channel 5	LINE / MICRO	MICRO doubled in front panel

Versátil mezclador de 5 canales de tamaño compacto, fácil de usar y completamente equipado para instalación y aplicaciones móviles. Se adapta a un amplio abanico de aplicaciones: bares, disco bares, iglesias, tiendas, salas de fitness, escuelas, salas de conferencias y reuniones, alquiler, montajes móviles... lugares en los que el espacio es limitado y los usuarios no son técnicos especializados.

CARACTERÍSTICAS PRINCIPALES

- Apto para montaje de sobremesa y rack 19" (3u. de altura).
- 5 Vías, 8 entradas LINE, 3 entradas MIC, 2 entradas PHONO.
- 2 Salidas MASTER independientes (1x XLR / 1x RCA) y una salida de grabación REC.
- Control de tonos de 3 bandas por canal.
- Sistema de preescucha, PFL. Talkover. Alimentación Phantom.
- Faders ECLER de 45 mm.

